

LEINOS 130

Woodworm Free

Application: Preventive open-pored wood stabiliser. Also for wood in roofed outdoor areas and wood in damp rooms.

Technical Characteristics: Prevents fungal and insect infestation. Also suitable for restoring (consolidating) old wood. Permeable to water vapour. Protects the wood from wood-destroying insects and fungi through physical-mechanical action and makes the wood unrecognisable to pests.

Color: Light ochre, cloudy.

Ingredients: Water, aluminium oxide, silicic acid, potassium palmitate, magnesium oxide, potassium chloride, fatty acids.

Package Sizes: 1l / 2,5l / 10l

Substrate and Preparation: The wood surface must be firm, clean, free of grease and dust, untreated and absorbent. The wood moisture content should be 15-20 %. Shake or stir the container well before use. Heavily infested wood should be filed down before treatment.

Processing: Brushing, spraying, dipping or trough impregnation. Ambient and surface temperature above 15 °C. In case of woodworm infestation, carefully and completely saturate all feeding holes, if necessary with a disposable sprayer. A. Application method 1. Brushing, spraying (at least 2 applications are required): Woodworm Free 130 must be applied two to three times to ensure a reliable effect. Cracks must be carefully re-treated by brushing. When spraying, allow for losses due to spray mist. 2. Dipping or trough soaking: Observe a soaking time of at least 30 minutes. Wet and moist wood requires an immersion time of up to 24 hours. 3. In case of woodworm infestation: Soak all visible feeding holes carefully and completely with Woodworm Free 130. B. Post-treatment If the surface is to be re-treated, make sure that Woodworm Free 130 has been applied to the entire surface and is completely dry. If necessary, remove crystallised material with a brush or damp cloth. Treat the interior with all LEINOS products based on oil or wax and the exterior with a weatherproof LEINOS product.

Drying Time: Follow-up treatment after approx. 24 hours when the wood is completely dry.

Consumption: Brushing, spraying: Approx. 100 ml/m² per coat. At least 2 coats are required! Dipping or trough impregnation: Approx. 15 l/m³.

Thinning and Cleaning Agents: Water and LEINOS Vegetable Soap 930.

Storage and Shelf Life: Stable for at least 2 years when originally sealed. Store in a cool, dry but frost-free place. Close container tightly.

Special Notes: VOC: 1 g/l, EU limit value: 30 g/l (cat. h). EAK: 08 01 20

Hazard statements: Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.



LEINOS 130

Woodworm Free

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 24. März 2026