

# LEINOS 150

## Impregnation Primer

**Application:** Diffusible primer for all absorbent exterior wood substrates. With film protection against fungal attack.

**Technical Characteristics:** The wood primer penetrates deep into the wood and provides optimum contact for subsequent coats. Light-coloured, absorbent substrates dry slightly darker. Deep impregnating. Hardens the wood.

**Color:** Transparent, brownish.

**Ingredients:** Linseed oil, wood oil, isoparaffins, iodopropynyl butyl carbamate, drying agents.

**Package Sizes:** 750ml / 2,5l / 10l

**Substrate and Preparation:** Stir the product carefully before use.

**Processing:** Apply undiluted and evenly with a brush. Rolling, spraying or dipping is also possible. Apply a full coat once. If shiny spots are still visible after approx. 20 minutes, spread them again with a brush. leave to dry for 16-24 hours. The primed substrate must be thoroughly dry before further treatment with another LEINOS product.

**Drying Time:** At 20 °C and 50-55 % relative humidity: approx. 16-24 hours. For reliable drying and to avoid odour formation, we always recommend using a fan to ensure sufficient air circulation on the surface of the coating during the drying phase.

**Consumption:** Approx. 60 - 80 ml/m<sup>2</sup> per coat - may vary depending on the absorbency of the substrate.

**Thinning and Cleaning Agents:** Clean with LEINOS Thinner 200 before drying.

**Storage and Shelf Life:** Stable for at least 2 years when originally sealed. Store in a cool, dry but frost-free place. Close container tightly.

**Special Notes:** Work materials soaked in product with oil that is not completely dry should be stored in an airtight metal container/water and then disposed of, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may give off a typical odour. Wear approved respiratory protection when using spraying equipment. Wear a fine dust mask when sanding! VOC content: 360 g/l, EU limit value: 700 g/l (cat. f).  
GISCODE: BSL40 / EAK: 08 01 11

**Hazard statements:** Repeated exposure may cause skin dryness or cracking. Contains 3-Iodo-2-propynyl-butylcarbamate. May produce an allergic reaction. Active ingredient: 3-Iodo-2-propynyl-butylcarbamate <0,6%. Harmful to aquatic life with long lasting effects. Contains: Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. May be fatal if swallowed and enters airways. Safety data sheet available on request.

# LEINOS 150

## Impregnation Primer

GHS-08 / Danger



**Precautionary statements:** Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility. Hotline for allergy sufferers: +49 4163 / 867 47-0

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 30. März 2026