

# LEINOS 220

## Primer Oil

**Application:** Primer for all absorbent wooden substrates indoors. However, application outdoors is not excluded if desired.

**Technical Characteristics:** Open-pored, without film protection against fungal attack and without UV protection. The Primer Oil penetrates deep into the wood and establishes optimum contact for further coats.

**Color:** Colourless to slightly yellowish. Woods are stained to varying degrees depending on the type of wood and growth.

**Ingredients:** Linseed oil, isoparaffins, drying agents.

**Package Sizes:** 750ml / 2,5l / 10l

**Substrate and Preparation:** The substrate must be dry (wood moisture content max. 14 %), solid, clean, free of grease and dust and absorbent. Pre-sand wooden surfaces with 120 grit on the outside and 150-180 grit on the inside in the direction of the fibres, depending on the type of wood and desired penetration depth. Ambient and surface temperature above 15 °C. Drying behaviour is delayed at lower temperatures. Stir the product carefully before use.

**Processing:** Apply undiluted and evenly with a glaze brush. Rolling, spraying or dipping is also possible.

**Drying Time:** The drying time is approx. 16-24 hours (at 20 °C, air humidity approx. 55 %). For reliable drying and to avoid odours, we always recommend using a fan to ensure sufficient air circulation on the surface of the paint during the drying phase.

**Consumption:** Approx. 60 - 80 ml/m<sup>2</sup> per coat, may vary depending on the absorbency of the substrate.

**Thinning and Cleaning Agents:** Clean tools with LEINOS Thinner 200 before drying. Product is ready to use.

**Storage and Shelf Life:** Stable for at least 2 years when originally sealed. Store in a cool, dry and sealed place.

**Special Notes:** Work materials soaked in product with oil that is not completely dry should be stored in an airtight metal container/water and then disposed of, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may give off a typical odour. Wear approved respiratory protection when using spraying equipment. Wear a fine dust mask when sanding! VOC: 400 g/l, EU limit value: 700 g/l (cat. f). GISCODE: Ö 60+ / EAK: 08 01 02

**Hazard statements:** Contains: Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or cracking. Safety data sheet available on request.

# LEINOS 220

## Primer Oil

GHS-08 / Danger



**Precautionary statements:** Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 30. März 2026