

# LEINOS 223

## Teak Oil

**Application:** Teak Oil is a high-quality oil resin treatment for all outdoor wood, such as fences, pergolas, children's play equipment, wooden decking, teak and garden furniture, etc. Very suitable for tropical woods such as Bangkirai. High-quality vegetable oils impregnate new wood and revitalise old wood.

**Technical Characteristics:** Quick and easy application. The natural oils penetrate deep into the wood. They keep it healthy and elastic and prevent it from drying out. Good refresher for wood that has already been oiled. No sanding required for recoating. No unpleasant odours. Resistant to saliva and perspiration in accordance with DIN 53 160.

**Color:** Colourless to slightly yellowish. Light-coloured, absorbent substrates dry slightly darker. Woods are stained to varying degrees depending on their growth.

**Ingredients:** Linseed oil, ricin oil, wood oil, isoparaffins, iodopropynyl butyl carbamate, drying agents.

**Package Sizes:** 0,25 l / 750ml / 2,5l

**Substrate and Preparation:** The substrate must be dry, solid, clean, free of grease and dust and absorbent. Completely remove old coats of varnish and opaque paint. Wood that has already turned grey should be sanded down to sound wood or pre-treated with LEINOS Anti-Greying Fluid 940. Allow pressure-impregnated wood to weather for one to two months and remove any salt efflorescence.

**Processing:** Coating. Do not apply at temperatures below 10 °C and stir well before use. Apply thinly and evenly. Avoid the formation of puddles.

**Drying Time:** At 20 °C and medium humidity dry after 6-8 hours, recoatable after 16-24 hours.

**Consumption:** Approx. 50 - 70 ml/m<sup>2</sup>, may vary depending on the absorbency of the substrate.

**Thinning and Cleaning Agents:** Product is ready to use. Thinning and cleaning of tools with LEINOS Thinner 200.

**Storage and Shelf Life:** Store in a cool place. Shelf life is at least 2 years if unopened.

**Special Notes:** Work materials soaked in product with oil that is not completely dry should be stored in an airtight metal container/water and then disposed of, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may give off a typical odour. Wear approved respiratory protection when using spraying equipment. Wear a fine dust mask when sanding! VOC content: 420 g/litre. EU limit value: 700 g/l (cat. f). EAK: 08 01 11 / GISCODE: BSL40

**Hazard statements:** Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Contains 3-Iodo-2-propynyl-butylcarbamate. May produce an allergic reaction. Active ingredient: 3-Iodo-2-propynyl-butylcarbamate <0,6%. Safety data sheet available on request.

**Precautionary statements:** Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility. Hotline for allergy sufferers: +49 4163 / 867 47-0



# LEINOS 223

## Teak Oil

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 25. März 2026