

LEINOS 230

Quick Sanding Primer

Application: Open-pored primer for highly absorbent substrates indoors, e.g. for end-grain parquet, cork or terracotta. Can also be used outdoors. Without fungal and UV protection.

Technical Characteristics: Water-repellent, water vapour permeable. Penetrates deeply and remains elastic. Not suitable as a layer-forming material!

Color: Transparent, slightly yellowish. Light-coloured woods dry slightly darker. Woods are stained to varying degrees depending on their growth. With all varnishes, a slight yellowing or dark yellowing occurs after some time.

Ingredients: Light-coloured, unbleached linseed oil, drying agents.

Package Sizes: 0,25 l / 750ml / 2,5l

Substrate and Preparation: The substrate must be dry, solid, clean, free of grease and dust, and absorbent. Pre-sand wooden surfaces with 150-180 grit in the direction of the grain.

Processing: Brushing, rolling, spraying. Room and surface temperature above 15 °C. Apply one full coat. Carefully remove the shiny residue after 20 minutes, otherwise there is a risk of sticking.

Drying Time: Dust-dry after 24-48 hours. Can be recoated after 2-4 days. For reliable drying and to avoid odours, we always recommend the use of a fan to ensure sufficient air circulation on the surface during the drying phase. Note for untreated substrates: Apply one full coat. After approx. 20 minutes, carefully remove the glossy excess, otherwise there is a risk of sticking. Then allow to dry for 24-48 hours. Can be recoated after approx. 2-4 days. Before further treatment with another LEINOS product, it must be ensured that the primed substrate is well dried and no longer absorbent in order to avoid impoverishment of the subsequent films and thus inferior surfaces!

Consumption: Approx. 50 - 70 ml/m² per coat, may vary depending on the absorbency of the substrate.

Thinning and Cleaning Agents: LEINOS Thinner 200 is a ready-to-use product.

Storage and Shelf Life: Stable for at least 2 years when originally sealed. Store in a cool, dry and sealed place.

Special Notes: Work materials soaked in product with oil that is not completely dry should be stored in an airtight metal container/water and then disposed of, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may give off a typical odour. Wear approved respiratory protection when using spraying equipment. Wear a fine dust mask when sanding! VOC content: 1 g/litre. EU limit value: 700 g/l (cat. f).
GISCODE: BSL10 / EAK: 08 01 11

Hazard statements: Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.



LEINOS 230

Quick Sanding Primer

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 25. März 2026