

# LEINOS 241

## Hard Oil Clear

**Application:** For universal use. For impregnating all absorbent interior surfaces (wood, cork, porous stone), especially in areas subject to heavy wear (e.g. floors, doors, worktops, etc.). The durability of the surface can be significantly increased with a final treatment with Hard Oil Special 245.

**Technical Characteristics:** Water-repellent, open-pored impregnation. Good fullness. Low yellowing. Not suitable for damp areas.

**Color:** Transparent, colourless to slightly yellowish. Light-coloured surfaces dry slightly darker.

**Ingredients:** Safflower oil stand oil, safflower oil, natural resin ester, isoparaffins, drying agents.

**Package Sizes:** 0,25 l / 750ml / 2,5l / 10l

**Substrate and Preparation:** The substrate must be dry, solid, absorbent, clean and free of resin and dust. Product is ready to use. Stir carefully before use!

**Processing:** Brushing, rolling, spraying, dipping. Room and surface temperature above 15 °C. The product should be applied in at least two coats. This can be done wet-on-wet: The second coat can be applied after a waiting time of 20-30 minutes. Important note: Irrespective of the application, the excess oil must be carefully removed approx. 30 minutes after the last application. Sprayability: Non-binding guide values: Airless: nozzle 0.20 mm, spray angle: approx. 30°-40°, filter approx. 100-180 meshes, high pressure: nozzle 0.20 mm, spray angle 30° filter 100-180 meshes, low pressure: nozzle 0.20 mm

**Drying Time:** At 20 °C and 50 % relative humidity: Dust-dry after approx. 8 hours. Tread-resistant and suitable for further treatment after at least 16-20 hours. For reliable drying and to avoid odour formation, we always recommend using a fan to ensure sufficient air circulation on the surface of the paint during the drying phase.

**Consumption:** Approx. 50-70 ml per m<sup>2</sup>, per coat.

**Thinning and Cleaning Agents:** LEINOS Thinner 200.

**Storage and Shelf Life:** Stable for at least 2 years when originally sealed. Store in a cool, dry place. Close opened containers tightly, decant leftovers into smaller containers.

**Special Notes:** Work materials soaked in product with oil that is not completely dry should be stored in an airtight metal container/water and then disposed of, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may give off a typical odour. Wear approved respiratory protection when using spraying equipment. Wear a fine dust mask when sanding! VOC content: 460 g/l, EU limit value: 700 g/l (cat. f).  
GISCODE: Ö 60+ / EAK: 08 01 02

**Hazard statements:** Contains: Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or cracking. Safety data sheet available on request.

# LEINOS 241

## Hard Oil Clear

GHS-08 / Danger



**Precautionary statements:** Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 24. März 2026