

LEINOS 249

Rapid Oil LF

Application: For one-time application on all interior wood. Not suitable for kitchen worktops, stairs and floors.

Technical Characteristics: Solvent-free, impregnating, layer-forming. Elastic, antistatic. Welding and saliva resistant according to DIN 53 160.

Color: Colourless, transparent.

Ingredients: Safflower oil, sunflower oil, linseed oil, wood oil, ricin oil, natural resin ester, beeswax, carnauba wax, micro wax, drying agents.

Package Sizes: 0,25 l / 750ml / 2,5l

Substrate and Preparation: The substrate must be dry, firm, clean and free of grease and dust. Shake well before use.

Processing: Apply cold or hot with a brush, at room air temperatures above 15 °C. Allow to soak in, polish in with a pad after a contact time of 1-24 hours. Intermediate drying is not possible as there is no surface dryer.

Drying Time: At 23 °C and 50 % relative humidity 24 hours. The supply of warm air considerably shortens the drying time.

Consumption: 1. Apply 10-15 ml/m², considerably less or more depending on the absorbency and surface condition of the substrate. Stir well. Carry out a test coat!

Storage and Shelf Life: Stable for at least 2 years when originally sealed. Store in a cool, dry and sealed place.

Special Notes: Work materials soaked in product with oil that is not completely dry should be stored in an airtight metal container/water and then disposed of, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may give off a typical odour. Wear approved respiratory protection when using spraying equipment. Wear a fine dust mask when sanding! VOC content: 1 g/l, EU limit value: 400 g/l (cat. e).
GISCODE: BSL10 / EAK: 08 01 11

Hazard statements: Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 24. März 2026