

LEINOS 254

Stone and Concrete Oil

Application: For impregnating and maintaining all absorbent tiles and chemically neutral concrete surfaces, such as terracotta, indoors and outdoors.

Technical Characteristics: Protects against general soiling, grease and oil. Suitable as joint protection for cement joints. Water-repellent and abrasion-resistant, does not noticeably stain the surface.

Color: Colourless.

Ingredients: Wood oil, linseed oil, ricin oil, sunflower oil, natural resin esters, isoparaffins, drying agents.

Package Sizes: 750ml / 2,5l

Processing: Stir carefully before use. Use a brush, cloth, roller or sponge. The surface must be dry, clean and free of grease and dust. Apply the stone oil with a brush or roller. After a penetration time of approx. 20-30 minutes, remove any excess oil from areas that are still absorbent and polish the surface dry with a cloth or pad. Apply another thin coat the next day and apply as described above. If necessary, apply a 3rd coat depending on the absorbency of the substrate. Important: No oil layer must remain on the surface!

Drying Time: Dry and recoatable after 4-6 hours (18-22 °C / 50-55 % relative humidity). Complete drying takes approx. 7-10 days. For reliable drying and to avoid odour formation, we always recommend using a fan to ensure sufficient air circulation on the surface of the paint during the drying phase.

Consumption: 20-50 ml/m² depending on the absorbency of the substrate.

Thinning and Cleaning Agents: Product is ready to use. Clean the tools with LEINOS Thinner 200.

Storage and Shelf Life: Store in a cool and tightly closed place. If a skin forms, remove it before reuse. Sieve the oil if necessary.

Special Notes: Work materials soaked in product with oil that is not completely dry should be stored in an airtight metal container/water and then disposed of, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may give off a typical odour. Wear approved respiratory protection when using spraying equipment. Wear a fine dust mask when sanding! VOC content: 420 g/l, EU limit value: 700 g/l (Cat: f). Giscode: Ö 60+ / EAK: 08 01 11

Hazard statements: Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.



LEINOS 254

Stone and Concrete Oil

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 25. März 2026