

LEINOS 259

Hard Oil Universal

Application: For open-pored priming and finishing of all absorbent, heavily used interior surfaces such as wooden and cork floors, stairs, unglazed clay and stoneware tiles, Sterling OSB boards, furniture surfaces, etc.

Technical Characteristics: Enhances the natural texture, deepens the colour of the treated surfaces and produces a silk-matt, hard-wearing and water-repellent finish that is largely resistant to yellowing. Tested in accordance with EN 71, Part 3, and for resistance to saliva and sweat in accordance with DIN 53160.

Color: Colourless to slightly yellowish. Light-coloured, absorbent substrates dry to a slightly darker shade. The degree of colouring in wood varies depending on how it has grown.

Ingredients: Linseed oil, wood oil-castor oil-stand oil, wood oil-stand oil, natural resin esters, isoparaffins, drying agents.

Package Sizes: 0,25 l / 750ml / 2,5l / 10l / 30l

Substrate and Preparation: The substrate must be dry, solid, clean, free from grease and dust, and absorbent. Pre-sand wooden surfaces using 150–180 grit sandpaper in the direction of the grain.

Processing: Brushing, rolling, spraying, dipping. Room and surface temperature above 15 °C. Apply three evenly thin coats using a sealing roller, allowing 6–8 hours' drying time between coats. Overhangs must be avoided or removed. No intermediate sanding is required. Waxed surfaces can be refinished with LEINOS Hard Oil Universal 259, provided the wax has been completely removed beforehand.

Drying Time: Dust-dry after approx. 6–8 hours. Firm to the touch after approx. 16–24 hours. To ensure the paint dries properly and to prevent odours, we always recommend using a fan to ensure adequate air circulation over the painted surface during the drying phase.

Consumption: Approx. 40–60 ml/m² per coat; this may vary depending on the absorbency of the substrate. Three coats are recommended.

Thinning and Cleaning Agents: The product is ready for use. Clean with LEINOS Thinner 200.

Storage and Shelf Life: Stable for at least 2 years when kept in the original, unopened container. Store in a cool, dry place, keeping the container sealed.

Special Notes: Store work materials impregnated with the product, which still contain oil that has not fully dried, in an airtight metal container or in water, and then dispose of them, as there is otherwise a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may cause a characteristic odour. When using spray equipment, wear approved respiratory protection. Wear a fine dust mask when sanding! VOC content: 460 g/l, EU limit: 700 g/l (Cat. f). EAK: 08 01 11 / GISCODE: Ö 60+

Hazard statements: Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.

LEINOS 259

Hard Oil Universal

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 15. September 2026