

LEINOS 259

Hard Oil Universal

Application: For open-pored priming and finishing of all absorbent, heavily used interior substrates such as wood and cork floors, stairs, unglazed clay and stoneware tiles, Sterling OSB boards, furniture surfaces, etc.

Technical Characteristics: Revitalises the natural structure, deepens the tint of the treated surfaces and produces a silky matt, hard-wearing and water-repellent surface that is largely resistant to yellowing. Tested in accordance with EN 71, Part 3 and for saliva and perspiration fastness in accordance with DIN 53160.

Color: Colourless to slightly yellowish. Light-coloured, absorbent substrates dry slightly darker. Woods are stained to varying degrees depending on their growth.

Ingredients: Linseed oil, wood oil-ricinene oil-stand oil, wood oil-stand oil, natural resin esters, isoparaffins, drying agents.

Package Sizes: 0,25 l / 750ml / 2,5l / 10l / 30l

Substrate and Preparation: The substrate must be dry, solid, clean, free of grease and dust and absorbent. Pre-sand wooden surfaces with 150-180 grit in the direction of the grain.

Processing: Brushing, rolling, spraying, dipping. Room and surface temperature above 15 °C. Apply 3 evenly thin coats with a sealer roller, with a drying time of 6-8 hours between coats. It is essential to avoid or remove any excess. No intermediate sanding necessary. Waxed surfaces can be recoated with LEINOS Hard Oil Universal 259 if the wax has been completely removed beforehand.

Drying Time: Dust-dry after approx. 6-8 hours. Tread-resistant after approx. 16-24 hours. For reliable drying and to avoid odours, we always recommend the use of a fan to ensure sufficient air circulation on the surface during the drying phase.

Consumption: Approx. 40-60 ml/m² per coat, may vary depending on the absorbency of the substrate. 3 coats are recommended.

Thinning and Cleaning Agents: The product is ready to use. Clean with LEINOS Thinner 200.

Storage and Shelf Life: Stable for at least 2 years when originally sealed. Store in a cool, dry and sealed place.

Special Notes: Work materials soaked in product with oil that is not completely dry should be stored in an airtight metal container/water and then disposed of, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may give off a typical odour. Wear approved respiratory protection when using spraying equipment. Wear a fine dust mask when sanding! VOC content: 460 g/l, EU limit value: 700 g/l (cat. f). EAK: 08 01 11 / GISCODE: Ö 60+

Hazard statements: Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.



LEINOS 259

Hard Oil Universal

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 24. März 2026