

LEINOS 262

Wood Varnish Mix for exterior use

Application: Weatherproof and waterproof, open-pored protection for exterior use, with film protection against fungal attack. For absorbent wooden surfaces: exterior windows and doors, fences, pergolas, roof overhangs, shingles, wooden panelling, wooden houses. Not suitable for children's toys.

Technical Characteristics: Glazing, water-repellent coating. Water vapour permeable. Tested according to ihd and ift Rosenheim guidelines for discolouration by mortar, water vapour permeability, compatibility with sealing profiles, resistance to weathering. Tested for migration behaviour according to DIN EN 71, part 3. saliva and perspiration resistant according to DIN 53160. not suitable for permanent, high water exposure. Not suitable for floors.

Color: Wood Varnish Mix can be coloured in 57 different shades. All colour shades can be mixed with each other.

Ingredients: Wood oil, ricin oil, linseed oil, natural resin ester, isoparaffins, micro wax, zinc oxide, mineral pigments, iodopropynyl butyl carbamate, drying agents.

Package Sizes: 750ml / 2,5l

Processing: Brush, roll or spray. Ambient and surface temperature above 15 °C. Sprayability (non-binding guide values): Airless: Working pressure: 100-150 bar, nozzle 0.20 mm, spray angle: approx. 30°-40°, filter approx. 100-180 meshes. High pressure: working pressure: 2.0-2.5 bar, nozzle 0.20 mm, low pressure: nozzle 0.20 mm.

Drying Time: Approx. 16-24 hours.

Consumption: Approx. 60-80 ml/m² per application. Apply sparingly to avoid drying problems!

Thinning and Cleaning Agents: LEINOS Thinner 200 is a ready-to-use product.

Storage and Shelf Life: Stable for at least 2 years when originally sealed. Store in a cool, dry and sealed place.

Special Notes: Work materials soaked in product with oil that is not completely dry should be stored in an airtight metal container/water and then disposed of, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may give off a typical odour. Wear approved respiratory protection when using spraying equipment. Wear a fine dust mask when sanding! Colour specifications and colour imprints are non-binding. Colour deviations are possible depending on the batch, substrate and printing technique. The dried original colour shade differs from the fresh colour shade in the container. A test coat with colour matching is therefore essential. Mix different batches of the same colour shade together. VOC content: 480 g/l, EU limit value: 700 g/l (cat. f). EAK: 08 01 11 / GISCODE: Ö 60+

Hazard statements: Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Contains 3-Iodo-2-propynyl-butylcarbamate. May produce an allergic reaction. Active ingredient: 3-Iodo-2-propynyl-butylcarbamate <0,6%. Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility. Hotline for allergy sufferers: +49 4163 / 867 47-0

LEINOS 262

Wood Varnish Mix for exterior use

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 30. März 2026