

# LEINOS 264

## Facade Stain

**Application:** Weather and water-resistant, open-pored protective and decorative coating for exterior wooden facades and walls.

**Technical Characteristics:** Glazing to opaque depending on application thickness. Very weather-resistant and colour-fast, permeable to water vapour. Block-resistant, therefore suitable for windows and doors.

**Color:** 712 silver grey, 713 silver anthracite.

**Ingredients:** Ricin oil - natural resin boiling, natural resin ester, wood oil - stand oil, kaolin, zinc oxide, alumina, micro wax, isoparaffins, silicic acid, natural asphalt, mineral pigments, iodo-2-propynyl-butylcarbamate, drying agents.

**Package Sizes:** 750ml / 2,5l

**Substrate and Preparation:** The substrate must be dry, solid, clean, grease-free, dust-free and absorbent. A fungus-inhibiting primer, e.g. with LEINOS Impregnation Primer 150, should be applied in advance.

**Processing:** Stir carefully before use. Brush, roll or spray. If necessary, the wood surfaces can be pre-sanded with 120 grit in the direction of the grain. The product can also be applied directly to rough sawn wood. We recommend priming with LEINOS Impregnation Primer 150, followed by 1-2 coats of Facade Stain 264. Allow each coat to dry thoroughly before continuing. Intermediate sanding is not necessary. To achieve optimum results, please observe the technical data sheets for all products used. The ambient and surface temperature during application should be above 12 °C.

**Drying Time:** Approx. 16-24 hours. This system requires sufficient quantities of atmospheric oxygen for drying.

**Consumption:** Approx. 40-60 ml/m<sup>2</sup> per application, equivalent to 16-25 m<sup>2</sup> per litre.

**Thinning and Cleaning Agents:** LEINOS Thinner 200 is a ready-to-use product. Stir thoroughly before use.

**Storage and Shelf Life:** Stable for at least 2 years when originally sealed. Store in a cool, dry and sealed place.

**Special Notes:** Work materials soaked in product with oil that is not completely dry should be stored in an airtight metal container/water and then disposed of, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may give off a typical odour. Wear approved respiratory protection when using spraying equipment. Wear a fine dust mask when sanding! Colour specifications and colour imprints are non-binding. Colour deviations are possible depending on the batch, substrate and printing technique. The dried original colour shade differs from the fresh colour shade in the container. A test coat with colour matching is therefore essential. Mix different batches of the same colour shade together. VOC content: 400 g/l, EU limit value: 700 g/l (cat. f). EAK: 08 01 11 / GISCODE: Ö60+

**Hazard statements:** Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Contains 3-Iodo-2-propynyl-butylcarbamate. May produce an allergic reaction. Active ingredient: 3-Iodo-2-propynyl-butylcarbamate <0,6%. Safety data sheet available on request.



# LEINOS 264

## Facade Stain

**Precautionary statements:** Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 24. März 2026