

# LEINOS 285.202

## Oil Refurbisher White

**Application:** For treating all oiled and waxed surfaces such as wood, cork and linoleum indoors, to prevent the formation of runways.

**Technical Characteristics:** Transparent, easy to apply. The open-pored, silk-matt, hard-wearing and water-repellent surface is non-yellowing. Tested for migration behaviour in accordance with DIN EN 71, Part 3. Welding and saliva resistant in accordance with DIN 53160.

**Color:** 202 White

**Ingredients:** Linseed oil, wood oil, ricin oil, natural resin ester, isoparaffins, zinc oxide, alumina, kaolin, talcum, micro wax, silicic acid, mineral pigments, drying agents.

**Package Sizes:** 0,25 l / 750ml / 2,5l / 10l

**Substrate and Preparation:** The substrate must be dry (wood moisture content max. 14 %) and free of dirt and grease. Clean with LEINOS Vegetable Soap 930 (wipe with a damp cloth). Neutralise with clear water. Allow the floor to dry thoroughly. The floor temperature during application must be at least 16°C.

**Processing:** Stir carefully before use! Oil Refurbisher is applied evenly and thinly with a short-pile floor wiper (mop). Remove excess oil after 15-20 minutes and polish the surface with a white pad. Heavily worn and worn, lean surfaces must be treated a second time with Oil Refurbisher. Heavily worn, stressed surfaces can also be treated with Hardwax Oil 290. Carry out a preliminary test! Ensure optimum fresh air circulation during application and drying! Oil wash: Depending on the degree of soiling and absorbency of the wood, spread 100-200 ml/m<sup>2</sup> evenly and leave to work for approx. 10 minutes. Then loosen the dirt with a green pad and carefully remove with a rubber lip or similar. Depending on the degree of soiling, this dirt solution can be reapplied approx. 2-3 times to the neighbouring surface. After the floor surface of a room has been cleaned, it is completely rubbed dry again with a white pad until there is no more excess. In order to achieve a uniform surface appearance, Oil Refurbisher can be applied very thinly with a white polishing pad after approx. 24 hours drying time. Carry out a preliminary test!

**Drying Time:** Dry, sandable and recoatable after 6-12 hours (20 °C, humidity 50-55 %). Floors can be carefully loaded after 1 day. Full load-bearing capacity after 7-14 days. This system requires atmospheric oxygen to dry. Therefore, ensure good ventilation, e.g. with a fan in stagnant air (also to avoid odours).

**Consumption:** Consumption and coverage depend on the absorbency of the substrate and the type of application. Maintenance approx. 30-40 ml/m<sup>2</sup>. Oil wash approx. 100-200 ml/m<sup>2</sup>. Determine exact consumption on the object.

**Thinning and Cleaning Agents:** Immediately after use with LEINOS Thinner 200.

**Storage and Shelf Life:** Store in a cool, dry but frost-free place. Close container tightly. Shelf life is at least 2 years if unopened. Any skin that may have formed must be removed before reuse.

# LEINOS 285.202

## Oil Refurbisher White

**Special Notes:** Work materials soaked in product with oil that is not completely dry should be stored in an airtight metal container/water and then disposed of, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may give off a typical odour. Wear approved respiratory protection when using spraying equipment. Wear a fine dust mask when sanding! Colour specifications and colour imprints are non-binding. Colour deviations are possible depending on the batch, substrate and printing technique. The dried original colour shade differs from the fresh colour shade in the container. A test coat with colour matching is therefore essential. Mix different batches of the same colour shade together. VOC content: 600 g/l, EU limit value: 700 g/l (cat. f). GISCODE: Ö 60+ / EAK: 08 01 11

**Hazard statements:** Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Safety data sheet available on request.

**Precautionary statements:** Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 30. März 2026