

# LEINOS 337

## Wood spatula

**Application:** High-quality Wood spatula in powder form for repairs and knotholes up to 15 mm deep. It is compatible with all surface finishes. Suitable for indoor and outdoor use.

**Color:** 420 white, 421 ash, 422 oak, 423 natural oak, 424 smoked oak, 425 knotty oak, 426 cherry, 427 beech, 428 black.

**Ingredients:** Calcium carbonate, calcium sulphate, mineral pigments, 1,2-benzisothiazol-3(2H)-one.

**Package Sizes:** 0,1 kg / 0,5 kg / 5 kg

**Processing:** Mix the powder with cold water in a ratio of 3 parts powder to 1 to 1.5 parts water. The mixture is ready for immediate use. Can be applied within 20 minutes. Re-sanding possible after approx. 45 minutes. Process at 5 °C to 30 °C room temperature.

**Consumption:** Depending on the application.

**Storage and Shelf Life:** Store in a cool, dry and sealed place. Can be kept indefinitely in its original sealed packaging if stored correctly.

**Special Notes:** EAK: 08 01 11 / GISCODE: CP1

**Hazard statements:** Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request.

**Precautionary statements:** Keep out of reach of children. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 24. März 2026