

LEINOS 340

Liquid Wax

Application: For quick and easy open-pore finishing and care of previously waxed or oiled surfaces made of wood, cork and stone indoors. Not suitable for floors and hard-wearing surfaces!

Color: Colourless to slightly yellowish.

Ingredients: Linseed oil, sunflower oil, carnauba wax, beeswax, isoparaffins, clay, drying agents.

Package Sizes: 0,25 l / 750ml / 2,5l / 10l

Substrate and Preparation: The substrate must be dry, solid, clean, free of grease and dust and must not be absorbent. Heat Liquid Wax in a water bath at low temperatures.

Processing: With a brush or cloth. Room and surface temperature above 15 °C. A. Coating structure for untreated or absorbent substrates: Prime with LEINOS Primer Oil 220 or LEINOS Hard Oil 240 and apply Liquid Wax 340 very thinly and evenly with a brush or non-linting cloth. After approx. 8-12 hours, polish in the direction of the fibres, either with a polishing brush or a soft cloth. B. Coating for surfaces in need of renovation: As under point A, for non-absorbent substrates without primer.

Drying Time: Approx. 12-24 hours For reliable drying and to avoid odours, we always recommend using a fan to ensure sufficient air circulation on the surface of the paint during the drying phase.

Consumption: Approx. 35-50 ml/m² per application. Apply sparingly to avoid drying problems!

Thinning and Cleaning Agents: LEINOS Thinner 200 is a ready-to-use product.

Storage and Shelf Life: Stable for at least 2 years when originally sealed. Store in a cool, dry and sealed place.

Special Notes: Work materials soaked in product with oil that is not completely dry should be stored in an airtight metal container/water and then disposed of, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may give off a typical odour. Wear approved respiratory protection when using spraying equipment. Wear a fine dust mask when sanding! VOC content: max. 450 g/l, EU limit value: 700 g/l (cat. f). EAK: 08 01 11 / GISCODE: BSL40

Hazard statements: Contains: Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or cracking. Safety data sheet available on request.

GHS-08 / Danger



Precautionary statements: Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.



LEINOS 340

Liquid Wax

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 24. März 2026