

# LEINOS 350

## Wall Wax Finish

**Application:** Finish for finishing surfaces that have been painted with Natural Resin Dispersion Paint 660, Scumble Filler 630 or Wall-Wipe Varnish 601. Not suitable for lime or Silicate Paint.

**Technical Characteristics:** Open-pored protective film made from natural raw materials. Protects designed surfaces against dirt and mechanical abrasion. Increases wipe resistance.

**Ingredients:** Nut oil, safflower oil, natural resin ester, micro wax, clay, isoparaffins, benzisothiazolinone, drying agents.

**Package Sizes:** 750ml / 2,5l

**Processing:** Apply sparingly with a towelling cloth, roller or brush. Room and surface temperature above 15°C.

**Consumption:** Approx. 35 ml/m<sup>2</sup> per application. Use sparingly to avoid drying problems.

**Thinning and Cleaning Agents:** LEINOS Thinner 200.

**Storage and Shelf Life:** Store in a cool but frost-free place. Close the container tightly after use.

**Special Notes:** VOC content: 430 g/l, EU limit value: 700 g/l (cat. f). EAK: 08 01 11 / GISCODE: Ö60+

**Hazard statements:** Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request.

**Precautionary statements:** Keep out of reach of children. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility. Hotline for allergy sufferers: +49 4163 / 867 47-0

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 25. März 2026