

# LEINOS 620

## Deep Sealer

**Application:** For priming highly or differently absorbent substrates before further treatment with LEINOS wall paints: 640 Casein Wall Paint 650 White Emulsion Paint 655 Clay Paint 656 Clay Mix 657 Clay Plaster Mediterranean 658 Clay Plaster Fine 660 Natural Resin Emulsion Paint 670 Natural Mix 680 Plaster-Effect Paint Mediterranean 685 Plaster-Effect Paint Fine

**Technical Characteristics:** Transparent primer. Very high vapour permeability.

**Color:** Almost colourless after drying.

**Ingredients:** Water, shellac soap, natural resin soap, carnauba wax, beeswax, cellulose, potash, benzisothiazolinone.

**Package Sizes:** 1l / 2,5l / 20l

**Substrate and Preparation:** Suitable substrates are neutral plasters, porous stone, plasterboard and old, firmly adhering coats of wall paint. The substrate must be dry, clean and free of dust and grease.

**Processing:** Brushing, rolling, spraying. Ambient and surface temperature above 15°C. As a primer, the product must be diluted 1:1 with water. Note: To achieve the full load-bearing capacity of the final coat, the substrate must still be moderately absorbent when applying the final coat.

**Drying Time:** 2 - 4 hrs.

**Consumption:** Approx. 60-100 ml/m<sup>2</sup> when diluted, depending on the absorbency of the substrate.

**Thinning and Cleaning Agents:** Water and LEINOS Vegetable Soap 930.

**Storage and Shelf Life:** Stable for approx. 12 months when originally sealed. Store in a cool, dry and sealed place. Protect from frost.

**Special Notes:** EAK: 07 06 01

**Hazard statements:** Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request.

**Precautionary statements:** Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility. Hotline for allergy sufferers: +49 4163 / 867 47-0

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 25. März 2026