

LEINOS 631

Vintage Wall Ground

Application: For exclusive, diffusion-open wall design in living areas.

Technical Characteristics: Transparent, semi-gloss.

Color: Transparent, almost colourless after drying without tinting. Can be coloured with LEINOS Pigment Concentrates 668. LEINOS Pearlescent Pigments 668 are only suitable for colouring Vintage Wall Ground to a limited extent.

Ingredients: Water, shellac soap, natural resin soap, carnauba wax, beeswax, methyl cellulose, talcum, calcium carbonate, alumina, benzisothiazolinone.

Package Sizes: 750ml / 2,5l

Processing: Colour LEINOS Natural Resin Emulsion Paint 660 with matching Pigment Concentrate 668, apply a primer coat to the substrate and allow to dry thoroughly. Tint Vintage Wall Ground 631 and apply as a base filler individually in different layer thicknesses. Immediately after application, dry the levelling compound with a hot air device (approx. 500 °C, approx. 400-500 l/min air volume) in circular movements on the surface until stress cracks appear. After a further 24 hours or so, the thoroughly dried surface can be finished with coloured Vintage Wall Ground or pigment concentrates with other colour nuances. Before applying the Vintage Finish, the wall must be sanded to achieve the desired result. This allows the different layers of colour to stand out thanks to the relief structure. Japanese spatulas or similar spatulas are suitable tools. Room and surface temperature above 15 °C. Tip: LEINOS recommends first trying out the filling on a coated sample panel in order to assess the choice of colour and technique.

Drying Time: Can be ploughed over after 2-3 hours, polishable after approx. 24 hours.

Consumption: Between 30 and 70 g/m² per coat, depending on the type of design and application method.

Thinning and Cleaning Agents: Water and LEINOS Vegetable Soap 930, product is ready to use.

Storage and Shelf Life: Stable for approx. 12 months when originally sealed. Store in a cool, dry and sealed place. Protect from frost!

Special Notes: The VOC content of this product is max. 1 g/l. The EU limit value is max. 30 g/l (category A from 2010). EAK 08 01 12 / GISCODE: M-DF 01

Hazard statements: Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility. Hotline for allergy sufferers: +49 4163 / 867 47-0

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship.



LEINOS 631

Vintage Wall Ground

With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 25.
März 2026