

LEINOS 632

Effect Spatula

Application: For an exclusive, vapour-permeable wall finish in the living area.

Technical Characteristics: Once fully dry, a transparent Scumble Filler with a metallic sheen. Vapour-permeable. Can be tinted with LEINOS Pigment Concentrates 668. LEINOS Pearl Glaze Pigments 668 are not suitable for tinting Effect Spatula 264.

Color: 632 Metallic Silver. Other colours available on request. Can be custom-tinted in combination with Pigment Concentrates 668. Exception: Pigment Concentrates in Sterling Silver 340 and Gold Satin 345.

Ingredients: Water, shellac soap, natural resin soap, carnauba wax, beeswax, methylcellulose, talc, calcium carbonate, clay, mineral pigments, benzisothiazolinone.

Package Sizes: 750ml / 2,5l

Substrate and Preparation: To achieve the best results, please refer to the technical data sheets for all products used. The substrate must be chemically neutral, sound, dry, clean, free from grease and dust, and free from any substances that might bleed through. Depending on the desired result, first prime the substrate with LEINOS Interior Smoothing and Texturing Filler 684 and Deep Sealer 620 diluted 1:1 with water. Alternatively, apply a full coat of White Emulsion Paint Plus 660 to achieve a finely textured substrate. Customise the colour of Effect Filler 632 by mixing in approximately 10% Pigment Concentrate 668. To achieve pastel shades, use half white Pigment Concentrate 668 and half another coloured Pigment Concentrate.

Processing: Room and surface temperature above 15 °C. A. Filling: Using a Japanese spatula or similar tool, apply a thin layer of the coloured Effect Spatula 632 using the desired technique. At least 2, preferably 3, coats should be applied. These may be in the same or different shades. The previous coat must be dry before applying the next one. B. Finishing: Once dry, the coloured wall can be polished to a elegant satin sheen using a lambswool polishing disc. Additional surface protection can be achieved by applying LEINOS Wall Wax Finish 350. Transparency and colour depth are significantly enhanced by waxing. C. Tip: LEINOS recommends first trying out the filling technique on a coated sample board to assess the colour choice and technique.

Drying Time: Can be coated again after 2–3 hours; can be polished after approx. 24 hours.

Consumption: Between 30 and 70 g/m² per pass, depending on the type of design and application method.

Thinning and Cleaning Agents: The product is ready for use. Clean the tools immediately after use with water and LEINOS Vegetable Soap 930.

Storage and Shelf Life: Stable for approx. 12 months when unopened. Store in a cool, dry place with the lid on. Protect from frost!

Special Notes: VOC content: 1 g/l, EU limit: 30 g/l (Cat. a). EAK: 08 01 12 / GISCODE: M-DF 03

Hazard statements: Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility. Hotline for allergy sufferers: +49 4163 / 867 47-0

LEINOS 632

Effect Spatula

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 16. September 2026