

LEINOS 632

Effect Spatula

Application: For exclusive, diffusion-open wall design in the living area.

Technical Characteristics: Transparent Scumble Filler with metallic lustre after drying. Permeable to water vapour. Can be coloured with LEINOS Pigment Concentrates 668. LEINOS Pearlescent Pigments 668 are not suitable for colouring Effect Spatula 264.

Color: 632 Metallic silver. Other colours on request. Can be individually tinted in conjunction with Pigment Concentrates 668. Exception: Pigment Concentrate in Sterling Silver 340 and Gold Satin 345.

Ingredients: Water, shellac soap, natural resin soap, carnauba wax, beeswax, methyl cellulose, talcum, calcium carbonate, clay, mineral pigments, benzisothiazolinone.

Package Sizes: 750ml / 2,5l

Substrate and Preparation: To achieve optimum results, please observe the technical data sheets for all products used. The substrate must be chemically neutral, solid, dry, clean, free of grease and dust and free of penetrating substances. Depending on the desired result, first prime the substrate with LEINOS Smoothing and Texturing Filler 684 and Deep Sealer 620 diluted 1:1 with water. Alternatively, apply a covering coat of Natural Resin Emulsion Paint 660 to achieve a finely textured substrate. Colour the effect filler 632 individually with approx. 10 % Pigment Concentrate 668. To achieve pastel shades, use half Pigment Concentrate 668 white and another coloured Pigment Concentrate.

Processing: Room and surface temperature above 15 °C. A. Filling: Using a Japanese spatula or similar, apply a thin layer of the coloured Effect Spatula 632 in the desired technique. At least 2, preferably 3 coats should be applied. This can be done in the same or different colours. The previous coat must be dry. B. Finishing: After drying, the coloured wall can be polished with a lambskin polishing disc to a silky sheen. Additional protection of the surface can be achieved by using LEINOS Wall Wax 350. Waxing considerably increases transparency and colour depth. C. Tip: LEINOS recommends first trying out the filler on a coated sample panel in order to be able to assess the choice of colour and technique.

Drying Time: Can be ploughed over after 2-3 hours, polishable after approx. 24 hours.

Consumption: Between 30 and 70 g/m² per coat, depending on the type of design and application method.

Thinning and Cleaning Agents: Product is ready to use. Clean tools immediately after use with water and LEINOS Pflanzenseife 930.

Storage and Shelf Life: Stable for approx. 12 months when originally sealed. Store in a cool, dry and sealed place. Protect from frost!

Special Notes: VOC content: 1 g/l, EU limit value: 30 g/l (cat. a). EAK: 08 01 12 / GISCODE: M-DF 03

Hazard statements: Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility. Hotline for allergy sufferers: +49 4163 / 867 47-0



LEINOS 632

Effect Spatula

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 24. März 2026