

LEINOS 637

Furniture Chalk Paint

Application: Opaque, diffusion-open chalk paint according to DIN EN 13300 with very good coverage, easy to apply and versatile in use. For interior surfaces subject to light wear, e.g. furniture, wall panelling, etc.

Technical Characteristics: Solvent-free, good filling and covering properties, easy to apply, very economical. Wash-resistant according to DIN/EN ISO 11998 and DIN EN 13300, class 3, wet abrasion class 3, tested according to EN 71-3.

Color: 630 Mint, 631 Ice blue, 632 Savannah, 634 Vanilla, 635 Cream, 636 Tuscan red, 637 Pacific blue, 638 Stone grey, 639 Dark grey, 640 White.

Ingredients: Water, chalk, titanium dioxide, talc, calcite, natural resins, starch ester polymer, methyl cellulose, isothiazolinone.

Package Sizes: 0,1 l / 750ml / 2,5l

Processing: Stir carefully before use! The substrate must be dry and free of dust and grease. Old coats of paint must be sanded down and removed completely if they are flaking. To make the surface even more hard-wearing, we recommend treating it with Wall Wax Finish. It can be applied by brush or roller. At room temperatures above 8 °C.

Drying Time: At 20 °C and 50 % relative humidity: Surface dry after approx. 1-2 hours. Completely dry after approx. 12 hours. This system requires a sufficient amount of atmospheric oxygen, a dry substrate and a relative humidity that is not too high. Therefore, only work on a dry substrate and ensure good ventilation, e.g. with a fan in stagnant air, to avoid odours.

Consumption: Approx. 80-120 ml/m² per application, may vary depending on the absorbency of the substrate. Determine exact consumption quantities by trial application on the object.

Thinning and Cleaning Agents: Rinse with water immediately after use.

Storage and Shelf Life: Stable for approx. 12 months when originally sealed. Store in a cool, dry and sealed place. Protect from frost!

Special Notes: Colour specifications and colour imprints are non-binding. Colour deviations are possible depending on the batch, substrate and printing technique. The dried original colour shade differs from the fresh colour shade in the container. A test coat with colour matching is therefore essential. Mix different batches of the same colour shade together. The VOC content of this product is max. 1 g/l. The EU limit value is max. 30 g/l (category "a" from 2010). EAK 08 01 20 / GISCODE: BSW20

Hazard statements: Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility. Hotline for allergy sufferers: +49 4163 / 867 47-0



LEINOS 637

Furniture Chalk Paint

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 25. März 2026