

LEINOS 658

Clay Plaster Fine

Application: Interior. For all absorbent, mineral-based substrates, coatings in drywall construction, on firmly adhered wallpaper and, in particular, for clay substrates.

Technical Characteristics: Solvent-free and vapour-permeable. Produces a matt, slightly textured finish and helps regulate humidity levels in the home. Reversible. Grain size approx. 0.015 mm.

Color: Cream white, matt, can be custom-tinted using LEINOS Pigment Concentrates 668.

Ingredients: Water, clay, chalk, cellulose, titanium dioxide, polyaspartic acid, talc, starch ester polymer, isothiazolinones.

Package Sizes: 2,5l / 10l

Substrate and Preparation: The substrate must be dry, solid, absorbent, clean and free of dust. If in doubt, carry out a test application and, if necessary, prime with LEINOS Deep Sealer 620.

Processing: Always stir thoroughly before use and whilst applying. Apply the paint evenly using a roller, brush or flat brush, working it in all directions. One coat is usually sufficient. Ensure the room is well ventilated whilst applying the paint and whilst it is drying.

Drying Time: At 20 °C and 50 per cent relative humidity: approx. 6–12 hours.

Consumption: 1 litre is enough for approx. 4–4.5 m².

Thinning and Cleaning Agents: The product is ready for use. Wash tools immediately after use with water and LEINOS Vegetable Soap 930.

Storage and Shelf Life: Store in a cool, dry and frost-free place. Unopened, it will keep for at least 1 year.

Special Notes: VOC content: 1 g/l, EU limit value: 30 g/l (Cat. a). EAK: 08 01 20 / GISCODE: M-DF 01

Hazard statements: Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility. Hotline for allergy sufferers: +49 4163 / 867 47-0

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 22. Oktober 2026