

LEINOS 695

Mould Protection Paint

Application: Indoors against mould, algae and fungal infestation. LEINOS Mould Protection Paint is ready-to-use, solvent-free, based on vegetable and mineral raw materials and open to diffusion.

Technical Characteristics: Solvent-free. The effect is based on a crystallisation process. This means that the colour ingredients are no longer available to organisms (mould, algae, fungi, etc.) as a source of food. The colour has a dry covering power. Damp areas on the wall become transparent. Due to its mode of action, the paint is not resistant to washing.

Color: White. Tinting with LEINOS pigment concentrates 668 possible.

Ingredients: Water, silicic acid, common salt, calcium sulphate, cellulose, starch, titanium dioxide and plant extracts.

Package Sizes: 1l / 2,5l

Substrate and Preparation: The substrate must be dry, free of dust and grease, stable and moderately absorbent, free of separating agents, cracks and efflorescence. Treat surface mould infestation beforehand with LEINOS Mould Exx 960.

Processing: At room temperatures above 12 °C. With roller or brush. Stir the paint well before use. Before drying, the paint looks like a non-covering coat. 2 coats are required for a reliable effect. Important: Structural damage, sources of moisture etc. must be repaired. Full opacity is only visible after drying.

Drying Time: At 23 °C and 50 % relative humidity. Dries after a few minutes - high humidity extends the drying time. 2. Coat after 2-3 hours.

Consumption: Depending on substrate and application technique. Guide value 1 litre is sufficient for approx. 6.5 m² per coat. Determine the exact value on the object.

Thinning and Cleaning Agents: The product is ready to use. Clean tools immediately after use with warm water and LEINOS Vegetable Soap 930.

Storage and Shelf Life: Store in a cool, dry and frost-free place. Shelf life is at least 1 year if unopened. Keep opened containers tightly closed.

Special Notes: VOC content: 1.0 g/l, EU limit value: 30 g/l (cat. a). EAK: 08 01 20 / GISCODE: M-DF 01

Hazard statements: Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship.



LEINOS 695

Mould Protection Paint

With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 24. März 2026