

# LEINOS 720

## Natural latex adhesive

**Application:** Natural resin adhesive is suitable for bonding the following floor coverings: Unbacked cork floor coverings, linoleum on jute backing, cork linoleum, wool cardboard, cellulose fibre boards, soft wood fibre boards, textile floor coverings with textile or latex backing, with latex foam backing and secondary backing, needle felt and natural rubber floor coverings. PVC-coated and veneered cork panels and cork parquet with a density of less than 480 kg/m<sup>2</sup> must not be laid with this adhesive.

**Technical Characteristics:** Natural resin adhesive is a ready-to-use dispersion adhesive made from natural raw materials. It can be diluted with water and is suitable for laying floor coverings on underfloor heating. (Observe the guidelines for heated floors). The adhesive complies with DIN 53269, 53275 and 54324 and is also suitable for chair castors.

**Ingredients:** Water, natural latex, natural resin ester, talc, defoamer, diatomaceous earth, starch, casein, benzisothiazolinone.

**Package Sizes:** 1 kg / 3 kg / 10 kg

**Substrate and Preparation:** The substrate must comply with DIN 18365, i.e. it must be level, dry and free of dust, dirt, grease and cracks. Pre-coat highly absorbent and sanding substrates with diluted adhesive. Mastic asphalt and anhydrite screed must be levelled. Substrates for cork parquet and linoleum must always be levelled. The cork tiles themselves must be acclimatised for at least 24 hours in the room to be covered (room temperature min. 18 °C, relative humidity max. 65 %) before laying in a closed package. Old floor coverings are not suitable as a substrate.

**Processing:** As supplied, the natural resin adhesive is applied evenly to the substrate with a B2/B3 notched trowel. The flooring is immediately laid into the adhesive bed and rubbed down evenly. Adhesive stains must be removed immediately with water. Cork parquet and linoleum must be re-rolled after 30-60 minutes using a multi-section floor roller. Suspended bays in the linoleum must be weighted down.

**Consumption:** Levelled floor 350-400 g/m<sup>2</sup> with B2 filler. Non-smoothed and highly absorbent floors as well as more structured flooring backs 400-450 g/m<sup>2</sup> with B3 filler.

**Thinning and Cleaning Agents:** Clean with water immediately after use. Remove dried-on residual soiling with Thinner.

**Storage and Shelf Life:** Store in a cool (not below 10°C) and dry place. Seal opened containers tightly!

**Special Notes:** GISCODE: D 1 / EAK: 08 04 10

**Hazard statements:** Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request.

**Precautionary statements:** Keep out of reach of children. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility. Hotline for allergy sufferers: +49 4163 / 867 47-0



# **LEINOS 720**

## **Natural latex adhesive**

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 24. März 2026