

LEINOS 815

Insulating Primer

Application: Insulating coating against watery penetrating substrates indoors. Very well suited as a substrate for commercially available wool and fibre plasters.

Technical Characteristics: Priming paint with good sealing effect. It produces a fine-grained, rough surface. This must be taken into account if Insulating Primer 815 is to be painted over with other LEINOS products.

Color: Natural white.

Ingredients: Linseed oil, wood oil, ricin oil, natural resin ester, isoparaffins, talcum, chalk, titanium dioxide, alumina, drying agents.

Package Sizes: 750ml / 2,5l / 10l

Processing: The substrate must be dry, clean, solid and free of dust and grease. Brushing, rolling (use a short-pile roller). Room and surface temperature above 15 °C. Paint low to normally absorbent plaster, concrete, cement, chipboard, gypsum fibreboard, metal and polystyrene boards with one full coat. Paint highly absorbent plaster, gypsum plasterboard, insulating fibreboard etc. twice. Check adhesion on non-absorbent substrates.

Drying Time: At 20 °C/50-55 % relative humidity: Dust-dry after 8-10 hours, can be painted over with Insulating Primer after approx. 24 hours. Can be recoated with wool plaster after approx. 48-72 hours. For two coats with Insulating Primer after 4 days at the earliest. Ensure good ventilation!

Consumption: Do not exceed 100 ml/m² per coat.

Thinning and Cleaning Agents: Product is ready to use. Cleaning of tools: With LEINOS Thinner 200.

Storage and Shelf Life: Stable for at least 2 years when originally sealed. Store in a cool, dry and sealed place.

Special Notes: Work materials soaked in product with oil that is not completely dry should be stored in an airtight metal container/water and then disposed of, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may give off a typical odour. Wear approved respiratory protection when using spraying equipment. Wear a fine dust mask when sanding! VOC content: 150 g/l, EU limit value: 400 g/l (cat. e). EAK: 08 01 02 / GISCODE: BSL10

Hazard statements: Repeated exposure may cause skin dryness or cracking. Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not



LEINOS 815

Insulating Primer

constitute a guarantee of product properties and does not establish a contractual legal relationship.
With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 25.
März 2026