

LEINOS 842

Finishing Lacquer Aqua Mix

Application: For timber used indoors and outdoors, as well as for dimensionally stable timber components such as windows and doors; for timber components with limited dimensional stability such as garden sheds, soffits and external gates; and for non-dimensionally stable timber components such as fences, carports and palisades. Also suitable as a renovation coat and as an intermediate and top coat. Not suitable for coating floor surfaces.

Technical Characteristics: Quick-drying, solvent-free, resistant to caking, low yellowing, high opacity and good edge coverage, easy to apply and with a silk-matt finish.

Color: Machine-tinted in accordance with the NCS or RAL colour palettes. All colours can be mixed together.

Ingredients: Plant-oil-based hybrid binder, titanium dioxide (Base 1 only), mineral pigments, additives, water, preservatives.

Package Sizes: 750ml / 2,5l

Substrate and Preparation: The product is ready for application. Stir thoroughly before use! The substrate must be dry, sound, clean, free from grease and dust. Test the product on small test areas to check its compatibility with and adhesion to the substrate.

Processing: During application and drying, protect surfaces from rain, wind, direct sunlight and condensation. Apply by brush, roller or spray. Between coats, lightly sand the primer and intermediate coat once dry (P180). Wear a dust mask when sanding! Vibrant, intense colours, e.g. yellow, red, etc., may naturally have lower hiding power due to the pigments used. An additional coat may be required if necessary. The final gloss level will be achieved 2–3 weeks after application.

Drying Time: Dust-dry after approx. 2 hours. Can be recoated after approx. 8–10 hours. Fully dry after approx. 3 days. At low temperatures, high humidity or if the maximum coat thickness is exceeded, the time taken to dry thoroughly may be significantly delayed.

Consumption: 70–100 ml/m², depending on the absorbency of the substrate.

Thinning and Cleaning Agents: Water.

Storage and Shelf Life: Stable for at least 2 years when kept in the original, unopened container. Store in a cool, dry place, keeping the container sealed.

Special Notes: VOC content: 70 g/l. EU limit value: 130 g/l (Cat. d). GISCODE: BSW30 / EAK: 08 01 11

Hazard statements: Enthält 1,2-Benzisothiazol-3(2H)-on; 1,2-Benzisothiazolin-3-on, Reaktionsmasse aus 5-Chlor-2-methyl-2H-isothiazol-3-on und 2-Methyl-2H-isothiazol-3-on (3:1). Kann allergische Reaktionen hervorrufen. Sicherheitsdatenblatt auf Anfrage erhältlich.

Precautionary statements: Ist ärztlicher Rat erforderlich, Verpackung oder Kennzeichnungsetikett bereithalten. Darf nicht in die Hände von Kindern gelangen. Beim Einsatz von Spritzgeräten einen zugelassenen Atemschutz tragen. Beim Schleifen Feinstaubmaske tragen! Entsorgen Sie keine Produktreste und reinigen Sie keine Werkzeuge in Waschbecken oder Abflüssen. Inhalt/Behälter einer ordnungsgemäßen Verwertung zuführen.

LEINOS 842

Finishing Lacquer Aqua Mix

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 15. September 2026