

LEINOS 855

Weatherproof Paint Water-Based

Application: Solvent-free, matt coating for all untreated exterior wooden structures. Well suited for rough sawn wood. Not suitable for oak wood!

Technical Characteristics: Good hiding power. Permeable to water vapour. Easy to renovate. With film protection against fungal attack.

Color: 014 Mashed yellow, 057 Swedish red

Ingredients: Water, linseed oil, rye flour, bentonite, ferrous sulphate, iron oxide pigments, potassium oleate, iodopropynyl butyl carbamate, drying agents.

Package Sizes: 2,5l / 10l

Substrate and Preparation: The substrate must be dry, solid, clean, free of grease and dust and must not be absorbent. Brush out untreated, rough-sawn wood beforehand.

Processing: The substrate must be dry, solid, absorbent, clean and free of resin and dust. Apply by brushing at an ambient and surface temperature above 10 °C. Product is ready to use. Stir carefully before use!

Drying Time: At 20 °C and 50 % relative humidity: dust-dry after approx. 2 hours. Dry and recoatable after approx. 24 hours.

Consumption: Approx. 55-85 ml/m² per coat on planed or sanded wood. The consumption is slightly higher for rough sawn wood. Apply sparingly to avoid drying problems!

Thinning and Cleaning Agents: Thinner with up to 20 % water. For cleaning, use water and LEINOS Intensive Cleaner 935 or LEINOS Thinner 200 for stubborn stains.

Storage and Shelf Life: Store in a cool and dry place. Shelf life is at least 2 years if unopened. Close opened containers tightly, decant leftovers into smaller containers.

Special Notes: Colour specifications and colour imprints are non-binding. Colour deviations are possible depending on the batch, substrate and printing technique. The dried original colour shade differs from the fresh colour shade in the container. A test coat with colour matching is therefore essential. Mix different batches of the same colour shade together. VOC content: 1 g/l, EU limit value: 30 g/l (cat. a). EAK: 08 01 20 / GISCODE: BSW50

Hazard statements: Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May cause allergic reactions. Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility. Hotline for allergy sufferers: +49 4163 / 867 47-0

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship.



LEINOS 855

Weatherproof Paint Water-Based

With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 24. März 2026