

LEINOS 860

Screed Paint

Application: Protection and colouring for all open-pored screed and concrete surfaces, especially for basement stairs and garage floors. Not suitable for treating sealed old surfaces or glazed tiles.

Technical Characteristics: Protects against general soiling, grease and oil. Suitable as joint protection for cement joints. Water-repellent and abrasion-resistant.

Color: 130 Beige, 715 Cement grey, 732 Anthracite grey.

Ingredients: Rizine oil-natural resin ester boiling, natural resin ester, mineral fillers, natural asphalt, isoparaffins, drying agents.

Package Sizes: 750ml / 2,5l / 10l

Substrate and Preparation: The substrate must be dry, clean, free of grease and dust and chemically neutral. Stir very thoroughly before use!

Processing: Apply as thinly as possible with a brush, cloth, roller or sponge, spread or remove any excess after 15-20 minutes. Allow to dry well and apply a second coat without intermediate sanding. Spread this coat well and, if necessary, spread or remove excess material again. Depending on the absorbency of the substrate, a third or even fourth coat may be necessary. The surface must look well sealed without a noticeable layer having formed. Carry out a preliminary test! Important: Ensure optimum fresh air circulation during application and drying of the products!

Drying Time: Dry and recoatable after 6-12 hours (18-22 °C/50-55 % relative humidity). Complete drying takes approx. 7-10 days. This system requires sufficient quantities of atmospheric oxygen for drying. For reliable drying and to avoid odour formation, we always recommend using a fan to ensure sufficient air circulation on the surface of the coating during the drying phase.

Consumption: 20-50 ml/m² depending on the absorbency of the substrate for the first coat. Subsequent coats approx. 20-25 ml/m².

Thinning and Cleaning Agents: Screed Paint 840 is ready to use. Clean tools immediately after use with LEINOS Thinner 200.

Storage and Shelf Life: Store in a cool and tightly closed place. If a skin forms, remove it before reuse. Sieve the oil colour if necessary.

Special Notes: Work materials soaked in product with oil that is not completely dry should be stored in an airtight metal container/water and then disposed of, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may give off a typical odour. Wear approved respiratory protection when using spraying equipment. Wear a fine dust mask when sanding! Colour specifications and colour imprints are non-binding. Colour deviations are possible depending on the batch, substrate and printing technique. The dried original colour shade differs from the fresh colour shade in the container. A test coat with colour matching is therefore essential. Mix different batches of the same colour shade together. VOC content: 310 g/l, EU limit value: 400 g/l (cat. e). EAK: 08 01 11

Hazard statements: Repeated exposure may cause skin dryness or cracking. Safety data sheet available on request.

Precautionary statements: Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.



LEINOS 860

Screed Paint

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 24. März 2026